VGF® H24SE

With ESM® 2 and emPact Emission Control System

415 - 738 BHP (310 - 550 kWb)

Technical Data

Cylinders	Inline 8
Piston displacement	1,462 cu. in. (24 L)
Compression ratio	8.6:1
Bore & stroke	5.98" x 6.5" (152 x 165 mm)
Jacket water system capacity	20 gal. (75 L)
Lube oil capacity	56 gal. (212 L)
Fuel Pressure Range	1.5 - 5 psi (10 - 34 kPa)
Starting system	120 psi max. air/gas 24V DC electric

Dimensions I x w x h inch (mm)	
96.5 (2,453) x 48 (1,218) x 68.4 (1,737)	

Weights Ib (kg)

8,300 (3,773)



The Waukesha® VGF® series of highspeed engines are built with the durability expected from a medium-speed engine. The SE family of VGF engines with ESM® 2 features the most advanced and comprehensive control capability in its class. Multiple options for AFR control, INNIO catalysts, and NOx ratings are available. Non-road EPA mobile and stationary certification is available direct from INNIO as part of the mobileFLEX product line. Additionally, system reliabilty and performance upgrades have been integrated into the turbocharging/ wastegate, oil filtration, oil cooling, crankcase breathing, and cylinder heads.

Waukesha's emPact Emission Control System combines an engine, catalyst, and air/fuel ratio control, factorydesigned for enhanced interaction and improved performance. It consists of a factory supplied catalyst, pre- and postcatalyst oxygen sensing, and differential temperature and pressure sensors.

The emPact display panel provides real-time engine operating parameters, including faults, alarms, logs, and shutdowns. Waukesha's emPact Emission Control System provides a one-stop shop for compliance and a simple method of obtaining and meeting emission permits.





VGF H24SE

Standard Features

Air inlet system

- · single, high capacity air filter
- service indicator
- · rain shield

Cooling systems

- gear-driven jacket & auxiliary water pumps
- engine-mounted thermostats
- jacket circuit at 200° F outlet
- auxiliary circuit at 130° F inlet

Engine control system

- Engine System Manager (ESM 2)
- Start/stop, governing, electronic throttle and fuel valve control, AFR, ignition, individual cylinder detonation protection, fault logging

- CSA class 1, division 2
- HMI (shipped loose)
- Modbus RS-485 communications

Exhaust system

- high altitude turbocharger
- water-cooled wastegate
- · water-cooled manifolds

Fuel system

- 24V on/off valve
- mounted pressure regulator
- full flow control valve
- carburetor (850-2350 Btu/scft LHV)
- dual carburetor optional

Lubrication system

- high capacity main filters
- mounted centrifuge
- high efficiency oil cooler
- closed crankcase breather
- high capacity oil pan

Mounting system

- · SAE 0 flywheel housing
- SAE18 flywheel
- base-style oil pan with four-point mount

Miscellaneous

- viscous vibration damper
- two access doors per cylinder
- · oil pan access doors

Optional Equipment

- · SAE14 flywheel
- CSA B149-compliant fuel system
- multiple length customer control harnesses
- · exhaust flex & silencers
- emPact emissions control at 0.15gr NOx +0.3gr CO
- emPact emissions control at 0.5gr NOx +1.0gr CO
- front and rear stub shafts
- 24V electric starter
- air/gas turbine air starter
- 24V, 50A engine-driven alternator

- inertial precleaner for air filter
- 24Vdc, 240Vac, and air/gas pre- and post-lube
- jacket water heating and circulation
- knockdown gas pressure regulator
- removal of engine driven water pumps
- oil leveler
- extra magnetic pickup
- CE mark
- crankshaft pulley

- exhaust thermocouples, including all harnesses & hardware to provide data via Modbus
- EPA non-road/mobile & stationary certification
- low Btu fuel system for 700-850 Btu LHV applications
- capability for NFPA110 Type 10



Waukesha - an INNIO Group brand - INNIO Group's Waukesha engines are at the forefront of the energy transition, providing reliable energy solutions for distributed gas compression and power generation applications. The brand's rich and lean-burn engines, ranging from 335 hp to 5,000 hp, set an industry standard for low emissions, high reliability, and fuel flexibility.

Waukesha products are continuously upgraded to help operators stay emission-compliant without sacrificing operational excellence. These upgrades include new and remanufactured engines and parts, as well as conversion and modification kits, all of which are backed by OEM warranty and more than 115 years of engine expertise. Additionally, Waukesha digital solutions include SkidlQ, a collaborative solution with Detechtion Technologies for gas compression applications and INNIO Group's Al-powered myPlant platform for power generation applications. Both solutions provide customers with enhanced monitoring and optimization capabilities, resulting in improved performance and reduced downtime.

The Waukesha team connects locally with its customers to enable a rapid response to their service needs, providing enhanced support through a broad network of distributors and solution providers with parts, services, and digital offerings.

Waukesha engines are engineered in Waukesha, Wisconsin, U.S., and manufactured in Welland, Ontario, Canada. To learn more about the company's products and services, please visit INNIO Group's Waukesha website at waukeshaengine.com or follow Waukesha engines on Linkedin.

IWK-123069-EN

